

20A, 100V Trench Schottky Rectifier

FEATURES

- Excellent high temperature stability
- Low forward voltage
- Low power loss/ High efficiency
- High forward surge capability
- RoHS Compliant
- Halogen-free


APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- DC to DC converters


MECHANICAL DATA

- Case: TO-220AB
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Mounting torque: 0.56 N·m maximum
- Meet JESD 201 class 2 whisker test
- Polarity: As marked
- Weight: 1.97g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
I_F	20	A
V_{RRM}	100	V
I_{FSM}	215	A
$T_J \text{ MAX}$	150	°C
Package	TO-220AB	
Configuration	Common cathode	



TO-220AB



ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ unless otherwise noted)			
PARAMETER		SYMBOL	VALUE
Repetitive peak reverse voltage		V_{RRM}	100
Reverse voltage, total rms value		$V_{R(RMS)}$	70
Forward current	per device	I_F	20
	per diode		10
Surge peak forward current, 8.3ms single half sine wave superimposed on rated load		I_{FSM}	215
Junction temperature		T_J	-55 to +150
Storage temperature		T_{STG}	-55 to +150

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance per diode ⁽¹⁾	$R_{\theta JL}$	1.3	°C/W
Junction-to-ambient thermal resistance per diode ⁽¹⁾	$R_{\theta JA}$	5.4	°C/W
Junction-to-case thermal resistance per diode ⁽²⁾	$R_{\theta JC}$	0.9	°C/W

Thermal Performance Notes:

- Units mounted on 4" x 6" x 0.25" Al-plate
- Mounted on infinite heatsink

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode ⁽¹⁾	$I_F = 5\text{A}, T_J = 25^\circ\text{C}$	V_F	0.65	-	V
	$I_F = 10\text{A}, T_J = 25^\circ\text{C}$		0.78	0.82	V
	$I_F = 5\text{A}, T_J = 125^\circ\text{C}$		0.56	-	V
	$I_F = 10\text{A}, T_J = 125^\circ\text{C}$		0.66	0.69	V
Reverse current @ rated V_R per diode ⁽²⁾	$T_J = 25^\circ\text{C}$	I_R	-	50	μA
	$T_J = 125^\circ\text{C}$		-	10	mA

Notes:

- Pulse test with $PW = 0.3\text{ms}$
- Pulse test with $PW = 30\text{ms}$

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TST20102C	TO-220AB	50 / Tube

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics






Fig.5 Typical Forward Power Dissipation vs. Forward Current



CHARACTERISTICS CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig.6 Typical Transient Thermal Characteristics



PACKAGE OUTLINE DIMENSIONS

TO-220AB



NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. PACKAGE OUTLINE REFERENCE:
JEDEC TO-220, VARIATION AB, ISSUE K.
4. THE DEFINED ZONE WHERE STAMPING AND SINGULATION IRREGULARITIES ARE ALLOWED. SLOT AND NOTCH MAY APPEAR IN THIS ZONE.
5. THIS DOES NOT INCLUDE MOLD FLASH. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREME OF THE PLASTIC BODY.
6. DWG NO REF: HQ2SD07-TO220AB-011 REV A.

MARKING DIAGRAM

G = Green compound
YWW = Date code
F = Factory code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.