

# **TSC Materials Composition Declaration**

Part Number:TQM2N7002KCU Part Weight Amount(g):0.0063 SCIP:N/A

Material Name	Substance Name	CAS No.	Raw Material Proportion	Proportion	ID	Exemption RoHS	Exemption ELV
Dice	Silicon(Si)	7440-21-3	99.726%	0.317%	PD-05		
	Tungsten(W)	7440-33-7	0.11%	]			
	Aluminum(Al)	7429-90-5	0.163%				
	Copper(Cu)	7440-50-8	0.001%	]			
Lead Frame	Silver(Ag)	7440-22-4	0.5%	45.519%	SL-48		
	Silicon(Si)	7440-21-3	0.01%				
	Copper(Cu)	7440-50-8	97.1%				
	Phosphorus(P)	7723-14-0	0.02%	]			
	Iron(Fe)	7439-89-6	0.06%				
	Nickel(Ni)	7440-02-0	0.7%				
	Tin(Sn)	7440-31-5	0.9%	]			
	Zinc(Zn)	7440-66-6	0.71%	]			
Molding	Carbon Black	1333-86-4	0.5%	52.04%	RM-07	Ì	
Compound	Silica Glass	60676-86-0	85.45%	]			
	Epoxy Resin A	Trade secret 2	6.6%	]			
	Poly[(O-Cresyl	29690-82-2	3.45%	1			
	Glycidyl Ether)-						
	Co-						
	Formaldehyde]						
	Phenol-	9003-35-4	4%	]			
	Formaldehyde						
	Resin						
Plating	Tin(Sn)	7440-31-5	100%	0.697%	PP-04		
Wire	Gold(Au)	7440-57-5	100%	1.427%	PW-14		

Tolerance ±10%

Created On: 2024-06-13

Materials Disclosure Disclaimer: TSC, based on its material content information provided by third-party suppliers, has taken and will continue to take reasonably diligent steps to provide any required or available information. TSC may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TSC and TSC suppliers may consider certain information to be proprietary, and thus certain information may not be available for release by TSC. Thus this information is provided only as estimates, and do not include trace levels of dopants and metal materials contained within devices in the finished products.



## **Safety Data Sheet**

#### 1.PRODUCT AND COMPANY IDENTIFICATION

• Part Number:TQM2N7002KCU

• Supplier Name: Taiwan Semiconductor Co., Ltd.

• Supplier Address: 11Fl., No. 205, Sec. 3, Beishin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C.

• Contact Tel/Fax: +886-2-8912-1588 / +886-2-8913-1788

#### 2.HAZARDS IDENTIFICATION

· Health Hazards: May cause an allergic skin reaction.

Flammability: NoneReactivity: None

#### 3.COMPOSITION/INFORMATION ON INGREDIENTS

Material Name	Substance Name	CAS No.	Raw Material Proportion	Proportion
Dice	Silicon(Si)	7440-21-3	99.726%	0.317%
	Tungsten(W)	7440-33-7	0.11%	
	Aluminum(Al)	7429-90-5	0.163%	
	Copper(Cu)	7440-50-8	0.001%	
Lead Frame	Silver(Ag)	7440-22-4	0.5%	45.519%
	Silicon(Si)	7440-21-3	0.01%	
	Copper(Cu)	7440-50-8	97.1%	
	Phosphorus(P)	7723-14-0	0.02%	
	Iron(Fe)	7439-89-6	0.06%	
	Nickel(Ni)	7440-02-0	0.7%	
	Tin(Sn)	7440-31-5	0.9%	
	Zinc(Zn)	7440-66-6	0.71%	
Molding Compound	Carbon Black	1333-86-4	0.5%	52.04%
	Silica Glass	60676-86-0	85.45%	
	Epoxy Resin A	Trade secret 2	6.6%	
	Poly[(O-Cresyl Glycidyl	29690-82-2	3.45%	
	Ether)-Co-Formaldehyde]			
	Phenol-Formaldehyde	9003-35-4	4%	
	Resin			
Plating	Tin(Sn)	7440-31-5	100%	0.697%
Wire	Gold(Au)	7440-57-5	100%	1.427%

#### **4.FIRST-AID MEASURES**

Oral Exposure: N/AInhalation Exposure: N/A

· Dermal Exposure: Wash off in flowing water or shower with soap. If irritation occurs, get medical attention.

• Eye Exposure: N/A

### **5.FIREFIGHTING MEASURES**

• Self-Ignition Temp.: N/A (Non self-ignition product)

• Flammability: N/A (Product is uninflammable.)

• Extinguishing Media:

• Suitable: Use water, carbon dioxide, dry chemical powder or appropriate foam if packing materials catch fire.

• Firefighting: Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eye and respiratory system.

• Specific Hazard(s): Emits toxic fumes under fire conditions.

#### **6.ACCIDENTAL RELEASE MEASURES**

- · Procedure(s) of personal precaution(s): Exercise appropriate precautions to minimize direct contact with skin.
- Methods for Cleaning Up: Sweep up, place in a bag and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete.

## 7.HANDLING AND STROAGE

within under 70%. The recommended uttermost storage period is 2 year. When transporting products from the storeroom and during the manufacturing process, the FCFC (first-in-first-out) condition should be observed.

#### **8.EXPOSURE CONTROLS / PERSONAL PROTECTION**

• Design of technical: N/A (IC are solid.)

• Occupational exposure: N/A

Personal Protection

· Respiratory protection: N/A

Hand protection: N/AEye protection: N/ABody protection: N/A

#### 9.PHYSICAL AND CHEMICAL PROPERTIES

5: ITTOIOAL AND OTTEINIOAL I NOT ENTILE	
Physical State	Solid
Odor	No odor
Specific Weight	N/A
Vapor pressure	N/A
Vapor density	N/A
Boiling po	N/A
Freezing point	N/A
Melting point	N/A
PH	N/A

#### **10.STABILITY AND REACTIVITY**

- Stability
- · Stable: Stable
- Material to Avoid: Strong oxidizing agents.
- Hazardous Decomposition Products: None
- Hazardous Polymerization: Will not occur.

#### 11.ECOLOGICAL INFORMATION

No data available.

## 12.TOXICOLOGICAL INFORMATION

Possibility of irritation	No
Possibility of allergic reaction	Possibility of allergic reaction Skin contact and irritation
Toxicity affecting the reproductive functions	No
Substance, which are toxic as a result of	N/A

#### 13.DISPOSAL CONSIDERATIONS

Waste disposal takes place with observance of all local and state laws. There are no special disposal procedures.

#### 14.TRANSPORT INFORMATION

Do not fling package with product.

## 15. REGULATORY INFORMATION

No particular. Please refer to the local regulatory information.

#### **16.INFORMATION**

	AT OTHER THOR		
	Supplier	Taiwan Semiconductor Co., Ltd.	
	Address	11Fl., No. 205, Sec. 3, Beishin Rd., Xindian Dist., New Taipei City 231,	
Γ	Contact Tel/Fax	(T) +886-2-8912-1588(F) +886-2-8913-1788	
	Date	2024-06-13	