

## Package View

Surface Mount package packed per EIA/JEDEC Standard RS-481, IEC60286-3



0603


## Packing Quantity

Packing Type	Packing Code	Packaging Description	Reel (pc)	Inner Box (pc)	Carton (pc)	Carton Size (mm) (Max)
Reel	RG	8 mm Tape, 7" Diameter Plastic Reel	4,000	20,000	120,000	397x216x232

## Component Orientation


Device Orientation and Direction of Feed

Unidirectional : Cathode Toward Sprocket Hole.




## Component Lateral Movement

Maximum lateral movement for punched and embossed carrier  
8 mm Tape




## Tape leader & trailer

- Unfilled leader and trailer pockets are sealed
- Leaders and trailers are taped to tape and hub, respectively, with masking tape
- All materials are static-dissipative



Trailer	Q'ty/Reel	Leader
Min 160 mm	4,000	Min 400 mm

## Embossed Carrier Tape Specification



**Note 1:** B1 is for tape feeder reference only, including draft concentric about Bo.

**Note 2 :** A0,B0,K0 are determined by component size. The clearance between the component and the cavity must be within 0.05mm(.002")min. to 0.65mm(.025")max. for 12mm tape, 0.05mm(.002")min to 0.90mm(.035")max. for 16mm tape. In addition, the components cannot rotate more than 20° within the determined cavity.


**Note 3:** Surface Resistance:  $\leq 10^7 \Omega$

ALL DIMENSION IN MILLIMETERS(Unit : mm)

Dim	Tape size	D0	E1	P0	P2	T	Ao	Bo	Ko
Spec	8mm	1.5 $\pm 0.1$	1.75 $\pm 0.1$	4 $\pm 0.1$	2 $\pm 0.05$	0.22 $\pm 0.03$	0.05~5.5	0.05~5.5	0.05~5.5

Dim	Tape size	B1	D1	F	W	P1	K	T1	T2
Spec	8mm	-	-	3.5 $\pm 0.05$	8 $\pm 0.2$	4 $\pm 0.1$	-	-	-

## Reel Specification



ALL DIMENSION IN MILLIMETERS (Unit : mm)

Reel Size	Tape size	A	B	C	D	N	G	T
7"	8mm	178±1	-	13±1	-	60±1	-	13.5max

Note : Surface Resistance :  $\leq 10^7 \Omega$