

Package View

Surface Mount package packed per EIA/JEDEC Standard RS-481, IEC60286-3



PDFN56U

Packing Quantity

Packing Type	Packing Code	Packaging Description	Reel (pc)	Inner Box (pc)	Carton (pc)	Carton Size (mm) (Max)	
Reel	ı Rı	12 mm Tape, 13" Diameter Plastic Reel	2,500	5,000	25,000	375x290x395	


Component Orientation

Device Orientation and Direction of Feed

Unidirectional: Pin 1 Toward Sprocket Hole.




User Direction of Feed






Component Lateral Movement

Maximum lateral movement for punched and embossed carrier 12 mm Tape



Tape leader & trailer


- Unfilled leader and trailer pockets are sealed
- Leaders and trailers are taped to tape and hub, respectively, with masking tape
- All materials are static-dissipative



Trailer	Q'ty/Reel	Leader		
Min 160 mm	2500	Min 400 mm		



Embossed Carrier Tape Specification



Note 1: B1 is for tape feeder reference only, including draft concentric about Bo.

Note 2: A0,B0,K0 are determined by component size. The clearance between the component and the cavity must be within 0.05mm(.002")min. to 0.65mm(.025")max. for 12mm tape, 0.05mm(.002")min to 0.90mm(.035")max. for 16mm tape. In addition, the components cannot rotate more than 20° within the determined cavity.


Note3: Surface Resistance 10⁴~10⁸ Ω


ALL DIMENSION IN MILLIMETERS(Unit: mm)

Dim	Tape size	D0	E1	P0	P2	Т	Ao	Во	Ko	
Spec	12 mm	1.5 +0.1, -0	1.75 ±0.10	4 ±0.10	2 ±0.05	0.35 max	6.9 max	5.4 ±0.20	1.03 ~1.5	
Dim	Tape size	B1	D1	F	W	P1	К	T1	T2	
Spec	12 mm	-	1.5 +0.25	5.5 ±0.05	12 ±0.3	8 ±0.1	-	-	-	





Reel Dimension






Tape with components shall pass around bending radius without damage, for reels with hub diameters. approaching minimum dimension.







ALL DIMENSION IN MILLIMETERS (Unit: mm)

Reel Size	Tape size	Reel diameter	Hole dimension	Hole dimension	Hole dimension	Hub diameter	Reel inner width (at the Hub)	Reel overall width	Reel inner width
		Α	В	С	D	N	W_1	W ₂	W_3
13"	12 mm	330 ±2.0	3.4 max	13.5 ±0.55	-	178 ±2	-	18.9 max	12.4 +2, -0

Note1: Surface Resistance $<10^{11} \Omega$